

Conexão Entrada do bico NPT ou BSP	MODELO			CAPACIDADE	Ø Nominal Orifício (mm)	Ø Máximo Passagem Livre** (mm)	VAZÃO										Ângulo de Pulverização	
	Montagem em Parede - MP						(litros por minuto)											
	BGF MP	BGM MP	BHF MP				0.7 Bar	1.5 Bar	2 Bar	3 Bar	4 Bar	5 Bar	6 Bar	7 Bar	10 Bar	1.5 Bar	6 Bar	
1/8	*	*		3	1.5	1.0	1.1	1.6	1.9	2.2	2.5	2.8	3.1	3.3	3.9	65°	59°	
	*	*		3.5	1.6	1.3	1.3	1.9	2.2	2.6	3.0	3.3	3.6	3.9	4.5	50°	46°	
	*	*		3.9	2.0	1.0	1.5	2.1	2.4	2.9	3.3	3.7	4.0	4.3	5.1	84°	79°	
	*	*		5	2.0	1.3	1.9	2.7	3.1	3.7	4.2	4.7	5.1	5.5	6.5	65°	59°	
	*	*		6.1	2.3	1.3	2.3	3.3	3.8	4.5	5.2	5.7	6.2	6.7	7.9	74°	68°	
¼	*	*		6.5	2.4	1.6	2.5	3.5	4.0	4.8	5.5	6.1	6.7	7.1	8.4	50°	46°	
	*	*		10	3.2	1.6	3.8	5.4	6.2	7.4	8.5	9.4	10.2	11.0	13.0	67°	61°	
	*	*		12.5	3.2	1.6	4.8	6.8	7.7	9.3	10.6	11.8	12.8	13.7	16.2	74°	68°	
⅜	*	*		9.5	2.6	2.4	3.6	5.1	5.9	7.1	8.1	8.9	9.7	10.4	12.3	50°	46°	
	*	*		15	3.6	2.4	5.7	8.1	9.3	11.2	12.7	14.1	15.4	16.5	19.4	67°	61°	
	*	*		20	4.0	2.8	7.6	10.8	12.4	14.9	17.0	18.8	20.0	22.0	26.0	80°	73°	
	*	*		22	4.5	2.8	8.4	11.9	13.6	16.4	18.7	21.0	23.0	24.0	28.0	90°	82°	
	*	*		16	3.5	3.2	6.1	8.7	9.9	11.9	13.6	15.1	16.4	17.6	21.0	50°	46°	
½	*	*		25	4.6	3.2	9.5	13.5	15.4	18.6	21.0	24	26.0	27.0	32.0	67°	61°	
	*	*		32	5.2	3.6	12.2	17.3	19.8	24.0	27.0	30.0	33.0	35.0	41.0	75°	68°	
	*	*		40	6.2	3.6	15.2	22.0	25.0	30.0	34.0	38.0	41.0	44.0	52.0	91°	83°	
	*	*		50	6.7	4.0	19.1	27.0	31.0	37.0	42.0	47.0	51.0	55.0	65.0	94°	86°	
¾				2.5	4.9	4.4	11.2	15.9	18.2	22.0	25.0	28.0	30.0	32.0	38.0	50°	46°	
		*	*	4	6.4	4.4	18.0	26.0	29.0	35.0	40.0	44.0	48.0	52.0	61.0	70°	63°	
		*	*	7	9.5	5.2	31.0	45.0	51.0	61.0	70.0	78.0	84.0	91.0	107	92°	84°	